

Bureau of Reclamation  
Mid-Pacific Region

California Department  
of Water Resources

# Upper San Joaquin River Basin Storage Investigation

## Workshop 5

April 30, 2003



# Workshop Purpose and Objectives

- ◆ Review comments on Draft Phase 1 In-Progress Report
  - ◆ Provide status of technical studies
  - ◆ Discuss alternatives development and evaluation
- 

# Workshop 5

## Agenda

### Welcome and Introductions

Investigation Overview

Conjunctive Use & Groundwater Storage

Surface Storage Options Screening

Alternatives Formulation and Feasibility Study Workplan

Next Steps

# Participation Principles

- ◆ Participate – Attend the workshops
  - ◆ Learn – Learn about resources, people, roles, and process
  - ◆ Represent – Bring issues and interests forward from others whose interests you share
  - ◆ Cooperate – Work with others in the workshops to share information and consider options
  - ◆ Educate – Report back to others who share your interests
-

# Workshop Ground Rules

- ◆ **Commit to being fully present**
  - No cell phones, pagers, voicemail, etc.
  - Ask for what you need from the meeting process and participants
- ◆ **Honor our time limits**
  - Keep comments and discussion concise
  - Stay focused on the topic – Use the parking lot for other issues
- ◆ **Respect each other**
  - Listen carefully to other participants
  - Respond to ideas and issues, not individuals
- ◆ **Support constructive discussion**
  - Suggest improvements and solutions
  - Build on others' ideas – Use “and” instead of “but”

# Workshop 5

## Agenda

Welcome and Introductions

**Investigation Overview**

Conjunctive Use & Groundwater Storage

Surface Storage Options Screening

Alternatives Formulation and Feasibility Study Workplan

Next Steps

# Investigation Scope & Goals

- ◆ **CALFED Goals for Upper San Joaquin River Basin Storage**
  - Contribute to restoration of San Joaquin River
  - Improve water quality in San Joaquin River
  - Facilitate conjunctive water management and water exchanges
- ◆ **CALFED Scope for Upper San Joaquin River Basin Storage**
  - An additional 250 - 750 TAF of storage in the upper San Joaquin River watershed through enlargement of Millerton Lake at Friant Dam or a functionally equivalent storage program


# STUDY AREA

- ◆ **Upper San Joaquin River Basin**
  - Headwaters to the Merced River
- ◆ **Eastern San Joaquin Valley**
  - CVP Friant Division
  - Groundwater basin





# Traditional Plan Development Approach



# Objectives for Phase 1 Appraisal Study

- ◆ **Scope of investigation**
  - Problems and opportunities
  - Planning approach
- ◆ **Range of initial storage options**
  - Screen options and estimate costs
  - Describe potential project accomplishments
  - Define project objectives
- ◆ **Begin formulating alternatives**
- ◆ **Define scope of Feasibility Study**

# Water Resources Problems and Opportunities

## ◆ Problems

- San Joaquin river ecosystem
- San Joaquin River water quality
- Groundwater overdraft
- Urban water quality

## ◆ Opportunities

- Flood control
- Hydropower
- Recreation
- Delta inflows


# Planning Approach for Phase 1 Appraisal Study



# Surface Storage Options

## Initial Screening Results

- ◆ 16 sites identified
- ◆ 2 sites already authorized for construction
- ◆ 7 sites dropped
- ◆ 7 sites retained



# Review and Comment Process

## ◆ Review Process

- Draft materials from team to participants
- Workshop discussion and document review at key milestones
  - ◆ Problems and Opportunities – Workshop #2
  - ◆ Surface Storage Options Screening – Workshop #3
  - ◆ In-Progress Phase 1 Report – Workshop #4
  - ◆ Alternatives Development – Currently
  - ◆ Draft Phase 1 Report -- Mid-2003

## ◆ Roles

- Participants provide oral and written comments to team
- Team incorporates comments or provides rationale for alternate approach, strategy, or conclusion

## Phase 1 Information Available To Date

- ◆ Workshop Summaries & Handouts
- ◆ Surface Storage Technical Memoranda
- ◆ Draft In-Progress Phase 1 Report
  
- ◆ All documents available on project website

[www.mp.usbr.gov/sccao/storage/index.html](http://www.mp.usbr.gov/sccao/storage/index.html)

---


# Types of Comments on Phase 1 Report

- ◆ **Range of Phase 1 Issues**
  - Study process
  - Conjunctive use
  - Surface storage projects
- ◆ **Many Comments Related to a Feasibility Study**
  - Operational assumptions for baseline and alternatives
  - Incremental alternative development
  - Cost and benefit calculations
  - Quantified objectives and evaluation criteria





# Comments on Study Process

- ◆ Consideration of water supply reliability
  - ◆ Ecosystem restoration objectives
  - ◆ Other project objectives
- 

# Workshop 5

## Agenda

Welcome and Introductions

Investigation Overview

**Conjunctive Use & Groundwater Storage**

Surface Storage Options Screening

Alternatives Formulation and Feasibility Study Workplan

Next Steps

# Comments Regarding Conjunctive Management and Groundwater Storage

- ◆ Overdraft conditions present an opportunity for groundwater storage
- ◆ Approach for integration of conjunctive management into Investigation is not clear
- ◆ Conjunctive management and groundwater storage should be considered for alternatives

# Integration of Conjunctive Management to Upper San Joaquin River Basin Storage Investigation

- ◆ **Identify opportunities and specific projects**
  - Similar to CALFED ISI Conjunctive Management Program
- ◆ **Screen specific projects**
  - Similar to approach used to screen surface storage projects
- ◆ **Include specific projects in Investigation**

# ISI Conjunctive Management Program

## ◆ Goals

- Help local agencies improve regional water supply reliability by increasing the coordinated use of surface water and groundwater

## ◆ Principles for project development

- Local planning and control
- Voluntary implementation
- Priority for in-basin water needs
- Compensation for out-of-basin transfers
- Basin-wide planning and monitoring

# ISI Conjunctive Management Program

MOU  
Between DWR  
and Local Entity

## Phase I Basin Assessment

- Guided by local advisory panel
- Establish basin objectives

## Phase II Project ID and Evaluation

- Project-specific feasibility study and environmental documentation
- Basin-wide modeling

## Phase III Project Implementation

- Local approval of feasible projects
- Subject to funding availability

# Storage Investigation Conjunctive Use Approach

## Step 1 Theoretical Opportunities

- Not project specific
- Based on available water supply
- Shows potential range

## Step 2 Identify Specific Projects

- Consistent with CALFED Principles
- Similar to Identification component of ISI Phase II

## Step 3 Evaluate Specific Projects

- Screen for inclusion in alternatives
- Similar to Evaluation component of ISI Phase II


Step 1  
Theoretical  
Opportunities

Step 2  
Identify Specific  
Projects

Step 3  
Evaluate Specific  
Projects

- ◆ **Identify available flood flows**
  - Post-Process CALSIM output
- ◆ **Determine range of recharge capacity**
  - Apply series of “screens” that constrain opportunities
- ◆ **Apply to Benchmark and alternatives**
  - Indicate how additional surface storage could facilitate additional conjunctive use





Step 1  
Theoretical  
Opportunities

Step 2  
Identify Specific  
Projects





Step 3  
Evaluate Specific  
Projects

◆ **CALFED Common Assumptions Inventory**

- Grant applications for studies and projects
- Previous project studies
- WEF Survey

◆ **Coordination with stakeholders**

- FWUA and member water districts
  - ISI Conjunctive Water Management Program
- 




**Step 1**  
**Theoretical Opportunities**

**Step 2**  
**Identify Specific Projects**

**Step 3**  
**Evaluate Specific Projects**



- ◆ **Local project proponent**
  - ◆ **Source and quantity of water**
  - ◆ **Facilities and lands**
  - ◆ **Operational assumptions and constraints**
  - ◆ **Institutional and implementation issues**
  - ◆ **Water developed at Friant Dam**
- 

# Potential Findings from Project Evaluations

- ◆ **Projects that are fully defined**
  - Add to list of storage options
  - Add to Without-Project Condition
  - Do not include in Investigation
  
- ◆ **Projects that are not fully defined**
  - Continue to monitor project development
  - Coordinate with ISI Conjunctive Management Program
  - Reconsider for alternatives when better defined

# CALSIM Baseline Simulation


## Theoretical Groundwater Storage

- ◆ Total flood flows available
- ◆ Range of groundwater recharge capacity
- ◆ Recharge reduction based on basin wetness
- ◆ Hypothetical reoperation to pre-deliver water
  
- ◆ Potential specific projects to recharge groundwater
- ◆ Potential recovery of stored water

**Today**  
Theoretical Groundwater  
Recharge Opportunity


**Future**  
Groundwater Storage  
Options for Evaluation

Step 1  
Theoretical  
Opportunities for  
Groundwater  
Storage




Flood Flows


Conveyance Capacity



Recharge Capacity




Basin Wetness Index




Theoretical  
Recharge  
Opportunity

# Flood Flows Released from Friant Dam



# Additional Groundwater Recharge Potential Based on Available Flow and Potential Available Recharge Capacity




# Wetness Index in CALSIM Baseline Simulation

- ◆ **Friant-Kern Canal Class 2 delivery is reduced based on Tulare Basin wetness**
  - Natural Flow of Tule River is used as wetness indicator
- ◆ **215 water (or Surplus Delivery) is not allocated when delivery is reduced due to basin wetness**
- ◆ **Assume ability to accept water for recharge would be limited based on wetness index**




# Additional Groundwater Recharge Potential Based on Available Flow and Available Capacity




# Annual Water Available for Recharge

Based on Available Flow, Available Capacity, and Wetness Index



# Monthly Operation of Millerton Reservoir

## Example for (Wet) Water Year 1938




# CALSIM Baseline Simulation


## Adjustment Based on Hypothetical Reoperation

- ◆ **Draw down reservoir at the end of the year**
  - Pre-deliver water to recharge basins October through January
- ◆ **Refill reservoir with winter flows**
  - Reduces flood spills
  - Wetness index limits recharge in this period
- ◆ **Use excess water that would have spilled in the spring**
  - Recharge when wetness allows

# Example of Hypothetical Reoperation for (Wet) Water Year 1938



# Theoretical Groundwater Recharge Potential



# Theoretical Recharge Analysis Findings

- ◆ **Theoretical recharge capacity is not significantly limited by canal conveyance capacity**
  - Canal capacity would limit recharge only at very high recharge rates
  - Results would be similar at any recharge location
- ◆ **Specific project details are needed for additional evaluation**
  - Each project will have additional operational criteria and constraints

# Workshop 5

## Agenda

Welcome and Introductions

Investigation Overview

Conjunctive Use & Groundwater Storage

**Surface Storage Options Screening**

Alternatives Formulation and Feasibility Study Workplan

Next Steps




# Types of Surface Storage Options

- ◆ **San Joaquin River Upstream of Friant Dam**
  - Similar to expansion of Millerton Lake
  - Includes pump-back storage above Millerton Lake
- ◆ **Exchange with Millerton Lake Water**
  - Pre-deliver water from Millerton Lake
  - Storage in another watershed to replace Millerton deliveries
- ◆ **Off-Canal Storage**
  - Gravity or pumped storage from Friant -Kern Canal

# Surface Storage Options Initial Sites Considered

## ◆ Reviewed previous studies


- USBR
- DWR
- Local Agencies
- NRDC/FWUA



# Surface Storage Options

## Initial Screening Results

- ◆ 16 sites identified
- ◆ 2 sites already authorized for construction
- ◆ 7 sites dropped
- ◆ 7 sites retained



# Status of Surface Storage Site Screening

## SAN JOAQUIN RIVER

- ◆ Enlarge Friant Retained
- ◆ Fine Gold Retained
- ◆ Temperance Flat Retained - multiple dam sites
- ◆ Enlarge Kerckhoff Include with Temperance Flat
- ◆ Enlarge Mammoth Pool Monitor progress by FWUA/SCE

## EXCHANGE

- ◆ Enlarge Pine Flat Dropped

## OFF-CANAL

- ◆ Yokohl Retained

# Surface Storage Options

## Estimated First Costs

- ◆ **Costs include**
  - Listed items
  - Unlisted items (10%)
  - Contingencies (25%)
  - Mitigation (5%)
  - Investigations, design, construction mgt. (15%)
- ◆ **Lands and easements costs not yet estimated**
  - Exception: Yokohl

# Surface Storage Options

## Estimated First Costs

Site	Storage Option	Max Surface Elevation (ft, msl)	New Storage (TAF)	Est. First Cost (\$M)
Friant	Raise 25 Ft	603	132	\$113
	Raise 60 Ft	638	340	\$266
	Raise 140 Ft	718	870	\$662
Temperance Flat (RM279)	New Reservoir (RCC Dam)	900	451	\$435
	New Reservoir (RCC Dam)	1100	1,273	\$771
Mammoth Pool	Enlarge Reservoir	3355	30	
Fine Gold	New Reservoir (RCC Dam)	900	133	\$161
	New Reservoir (RCC Dam)	1100	780	\$428
Yokohl Valley	New Reservoir (F-K Canal source)	791	450	\$294

# Modeling Summary From Workshop #4

- ◆ **Developed Benchmark**
  - ◆ Friant operations logic in CALSIM II model
  - ◆ Logic developed from review of historical operations
  - ◆ Appropriate as Benchmark for comparison
- ◆ **Single-purpose analyses for surface storage options**
  - ◆ San Joaquin River restoration
  - ◆ San Joaquin River water quality
  - ◆ Water supply reliability

# Single Purpose Analyses Assumptions

- ◆ Annual reservoir operation
- ◆ Existing flood space rules
- ◆ New supply used for one purpose only
- ◆ Benchmark average deliveries for each year type maintained in restoration and water quality analyses



# Summary of Single Purpose Analysis Results

Storage Options	Size	Additional Single-Purpose Release from Friant Dam		
		WS	RF	WQ
Friant Enlargement	700	134	140	134
	450	98		
	340	73		
	250	56		
	125	27		
Mammoth Pool	35	8		
Temperance Flat	1,273	163	171	181
	2,100	189	210	222
Fine Gold	800	117	124	124
	400	69		
	350	54		
	133	36		
Yokohl Creek	800	115	127	121
	400	74	76	69
Pine Flat	124	23		


Expected long-term average similar to WS

Expected long-term average similar to WS

Expected long-term average similar to WS

Long-term average of WS, RF, and WQ are similar

# Single Purpose Analysis Results



- ◆ Based on the results of Single Purpose - WS for Phase 1 Investigation
- ◆ Subject to Phase I modeling assumptions:
  1. Annual reservoir operation
  2. Pump/release capacity and operating schedule for pump-storage options
  3. Exchange schedule for Pine Flat option

# Single Purpose Analyses Findings

- ◆ Additional storage increases Class 2 water allocation and reduces available temporary flood water
- ◆ Additional water supply at Friant Dam is similar in all three single purpose evaluations
- ◆ Difficult to support new river demands in critical years
- ◆ Potential system impacts
  - Flood damage reduction
  - Same delivery to Mendota Pool, but different source mix

# Sensitivity Analyses Suggested at Workshop #4

- ◆ **On Benchmark**
  - Modeling time step (monthly vs. daily)
- ◆ **On Single Purpose Analyses**
  - Off-stream storage pumping / release capacity
  - Demand pattern for river restoration
  - Carryover storage operation to provide water for river releases in critical years

# Sensitivity Analyses on Time Step

## Monthly vs. Daily Operation

### ◆ Issues


- Flood operation requires daily or hourly simulation
- Representation of flood release as monthly volume
- Options subject to results of flood operation may be sensitive to the modeling time-step
- Examples include conjunctive use and off-stream storage along the Friant-Kern Canal

### ◆ Approach in Sensitivity Analysis

- Historical monthly vs. daily
- CALSIM results vs. historical monthly


# Sensitivity Analyses on Time Step

Example - Potential water supply for conjunctive use




# Sensitivity Analyses on Time Step

Example - Potential water supply for conjunctive use



# Sensitivity Analyses on Time Step

Example - Potential water supply for conjunctive use





# Findings from Time Step Sensitivity Analysis








- ◆ **Use of monthly volume may overestimate available supply for canal diversions**
  - Conjunctive use opportunities
  - Off-canal storage
- ◆ **Difference is not significant for appraisal-level study**
- ◆ **Feasibility Study modeling needs**
  - Shorter time steps for flood control and hydropower
  - Refine operational assumptions

# Sensitivity Analyses Suggested at Workshop #4

- ◆ **On Benchmark**
  - Modeling time step (monthly vs. daily)
- ◆ **On Single Purpose Analyses**
  - Off-stream storage pumping / release capacity
  - Demand pattern for river restoration
  - Carryover storage operation to provide water for river releases in critical years

# Sensitivity Analyses on SPA Evaluations

## Summary of Simulated Options


Storage Options	Size	
Friant Enlargement	700	 
	450	
	340	
	250	
	125	
Mammoth Pool	35	
Temperance Flat	1,273	 
	2,100	
Fine Gold	800	  
	400	
	350	
	133	
Yokohl Creek	800	
	400	
Pine Flat	124	

### Sensitivity Analysis

-  Pump / release capacity for off-stream storage
-  River restoration demand pattern
-  Carry over storage for new river demand

# Sensitivity Analysis

## Pump and Release Capacity for Off-Stream Storage



# Pump and Release Capacity Sensitivity Analysis

## Findings from Fine Gold 800 TAF Simulations

- ◆ Results for all three single purpose analyses are similar
- ◆ Sensitivity to changes in pump / release capacity is small
- ◆ Similar results expected for off-canal storage (Yokohl)

Annual Average Release at Friant Dam for SPA (TAF)


	Pumping / Release Capacity (cfs)		
	2,000 / Unrestricted	2,000 / 2,000	3,000 / 3,000
FG-800			
WS	117	117	125
WQ	124	124	137
RF	124	124	133

# Sensitivity Analyses Suggested at Workshop #4


- ◆ **On Benchmark**
  - Modeling time step (monthly vs. daily)
- ◆ **On Single Purpose Analyses**
  - Off-stream storage pumping / release capacity
  - **Demand pattern for river restoration**
  - Carryover storage operation to provide water for river releases in critical years

# Sensitivity Analysis


## Restoration Pattern




**Single Purpose Analysis:**  
SJR unimpaired flow distribution



## Uniform distribution

 **Assumed constant loss rate (6 TAF per month) for all year types**

 **Year-type varying demand**



# Restoration Pattern Sensitivity Analysis

## Findings from Three Simulations

- ◆ Single Purpose Analysis results are not sensitive to changes in monthly restoration flow distribution

Annual Average Restoration Release at Friant Dam (TAF)

Options	Restoration Flow Pattern	
	SJR Unimpaired Flow Distribution	Uniform Distribution
FR-700	142	141
TF-1273	171	173
FG-800	124	120




# Sensitivity Analyses Suggested at Workshop #4

- ◆ **On Benchmark**
  - Modeling time step (monthly vs. daily)
- ◆ **On Single Purpose Analyses**
  - Off-stream storage pumping / release capacity
  - Demand pattern for river restoration
  - **Carryover storage operation to provide water for river releases in critical years**

# Carryover Storage Sensitivity Analysis

## Water Allocation for Annual Reservoir

NOT TO SCALE




- ◆ Dynamic allocation
- ◆ Based on hydrologic conditions and reservoir storage

- ◆ Prescribed for water quality or restoration flow purpose
- ◆ Based on a year-type-varying demand patterns

# Carryover Storage Sensitivity Analysis

## Water Allocation with Carryover Requirement


NOT TO SCALE



# Carryover Storage Sensitivity Analysis

## Criteria for Carryover Objective

- Results show difficulty in supplying river demand in critical years



# Carryover Storage Sensitivity Analysis




## Criteria for Carryover Objective

One-year carryover objective set at 140 TAF

Water Year	Year Type by San Joaquin Valley Index	Carryover Amount Units	Carryover Amount (TAF)	
⋮	⋮	⋮	⋮	
1927	Above Normal	2	280	} <b>2 carryover units target</b>
1928	Below Normal	2	280	
1929	Critical	1	140	} <b>Beginning of drought, 1 carryover unit</b>
1930	Critical	0	0	
1931	Critical	0	0	} <b>Into drought, no carryover</b>
1932	Above Normal	1	140	
1933	Dry	0	0	} <b>Into drought, no carryover</b>
1934	Critical	0	0	
1935	Above Normal	1	140	} <b>Out of drought, 1 carryover unit</b>
1936	Above Normal	2	280	
1937	Wet	2	280	} <b>2 carryover units target</b>
⋮	⋮	⋮	⋮	

# Carryover Storage Sensitivity Analysis

## Example Carryover Operation




# Carryover Storage Sensitivity Analysis Findings

- ◆ **Total water available for river demand is decreased**
  - Long-term annual average amount reduced about 30%
- ◆ **Ability to make river releases is shifted by year type**
  - Objective of carryover was to provide water in critical years
  - Problem shifted to above normal or below normal years

# Carryover Storage Sensitivity Analysis Findings


## Effect on Restoration Releases





# Carryover Storage Sensitivity Analysis Findings

## Effect on Water Quality Releases



# Sensitivity Analyses Conclusions

- ◆ **Sensitivity Analysis Findings**
  - Time step - minor, limited to specific analyses
  - Off-stream pump / release rates - minimal
  - Restoration pattern - insignificant
  - Carry-over operations - very significant
- ◆ **Operational Assumptions will be Important in Alternatives**
  - Preservation of Benchmark deliveries
  - Basis for carry-over requirements - risk-based analysis
  - Flood control rules

# Workshop 5

## Agenda

Welcome and Introductions

Investigation Overview

Conjunctive Use & Groundwater Storage

Surface Storage Options Screening

**Alternatives Formulation and Feasibility Study Workplan**

Next Steps

# Range of Comments on Options and Alternatives

- ◆ **Alternatives formulation**

- Functional equivalence
- Baseline assumptions

- ◆ **Environmental impacts**

- ◆ **Economics**

- Project cost
- Incremental analysis
- Beneficiaries pay

# What does “Functional Equivalence” mean?

- ◆ **Anything that provides water?**
  - Other CALFED Programs address non-storage actions
- ◆ **Storage options only?**
  - Surface Storage
  - Groundwater Storage
- ◆ **Similar accomplishments to a specific project?**
  - Friant Enlargement 250 - 700 TAF
  - Increase additional supply at Friant Dam

# Functional Equivalents

*Storage options that provide additional water supply at Friant Dam to support CALFED objectives for Upper San Joaquin Storage*




# Functional Equivalence Framework

## Performance Measures for Phase 1 Evaluation

- ◆ Derived from CALFED objectives for Upper San Joaquin Storage
  - ◆ Method to organize results of operational studies
  - ◆ Compare options and develop alternatives
-

# Functional Equivalence Framework





# Alternatives Formulation Approach

## ◆ Identify increments for storage options

- Enlarge Friant 125 to 870 TAF
- Fine Gold 125 to 800 TAF
- Temperance Flat 425 to 2,100 TAF
- Yokohl 400 to 800 TAF
- Conjunctive use projects As defined

## ◆ Calculate cost and yield for each increment

- Some options will require additional cost information

# Alternatives Formulation Approach

- ◆ **Initial alternatives based on major options**
  - Surface storage options
  - Conjunctive use projects
  
- ◆ **Incremental analysis**
  - Add reasonable project increments
  - Identify economic breakpoints

# Workshop 5

## Agenda

Welcome and Introductions

Investigation Overview

Conjunctive Use & Groundwater Storage

Surface Storage Options Screening

Alternatives Formulation and Feasibility Study Workplan

Next Steps

## Next Steps

- ◆ Temperance flat options review
- ◆ Hydropower evaluation
- ◆ Conjunctive use project identification
- ◆ Draft phase 1 report
- ◆ Feasibility Study Work Plan

# Temperance Flat Options

- ◆ **Options addressed in In-Progress Report**
  - 274, 279, 280 Sites described
  - 279 Site representative - considered construction issues
  - 280 Site dropped - similar to but less effective than 279
- ◆ **Additional options to be considered in Phase 1**
  - 274 and 286 Sites
  - Construction, environmental, hydropower issues

# Hydropower Evaluation

- ◆ **Impacts to existing power facilities**
  - Generation loss
  - Potential mitigation actions
  
- ◆ **Potential use and generation for new facilities**
  - Power plant opportunities
  - Estimated pumping for off-stream storage sites
  - Estimated generation at all sites

# Conjunctive Use Project Identification

- ◆ **Review CALFED Common Assumptions Inventory**
- ◆ **Stakeholder coordination**
  - Clarify project details
- ◆ **Identify operations assumptions**
- ◆ **Determine whether project should be included**
  - Without Project Condition
  - Alternatives

# Phase 1 Report Summary

- ◆ **Problems and opportunities**
- ◆ **Identify and screen storage options**
  - Surface storage sites
  - Conjunctive use approach
- ◆ **Costs and initial benefits of retained options**
- ◆ **Describe initial alternatives**
- ◆ **Provide focus for Feasibility Study**



# Feasibility Study Work Plan

- ◆ **Describe initial range of alternatives**
- ◆ **Technical studies**
  - Model development and application
  - Field activities
- ◆ **Methodologies to identify costs and benefits**
  - Water supply
  - Ecosystem
  - Water quality
  - Flood control
  - Hydropower

# Feasibility Study Activities

- ◆ Issue NOI/NOP
  - ◆ Formulate and evaluate alternatives
  - ◆ Identify recommended plan
  - ◆ Draft FS Report and EIS/EIR
  - ◆ Final FS Report and EIS/EIR
-

Bureau of Reclamation  
Mid-Pacific Region

California Department  
of Water Resources

# Upper San Joaquin River Basin Storage Investigation


## Workshop 5

April 30, 2003


# ISI Conjunctive Management Program

- ◆ **MOU Between DWR and Local Entity**
  - ◆ **Phase I - Basin Assessment**
    - Local advisory panel
    - Establish basin objectives
  - ◆ **Phase II - Project Identification and Evaluation**
    - Basin-wide modeling
    - Feasibility studies and environmental documentation
  - ◆ **Phase III - Project Implementation**
    - Local approval of feasible projects
    - Subject to funding availability
-


# Measuring Functional Equivalence



# Measuring Functional Equivalence (continued)



# Measuring Functional Equivalence (continued)



# Carryover Storage Sensitivity Analysis Findings

Total water available for river demand is decreased

Annual Average Release at Friant Dam in SPA (TAF)

Options	No Carryover WQ	With Carryover WQ	No Carryover RF	With Carryover RF
FR-700	134	100	142	99
TF-1273	181	153	171	154
FG-800	124	93	124	98

Average End-of-September Friant Unit Total Storage (TAF)

Options	No Carryover WQ	With Carryover WQ	No Carryover RF	With Carryover RF
FR-700	398	547	464	626
TF-1273	589	790	672	848
FG-800	464	611	532	664



# Carryover Storage Sensitivity Analysis Findings

## Ability to make river releases is shifted by year type

Percentage of Time with Release at Friant Dam in SPA

**FR-700**

San Joaquin Valley Index	No Carryover WQ	With Carryover WQ	No Carryover RF	With Carryover RF
Wet	100%	90%	100%	90%
Above Normal	100%	86%	100%	0%
Below Normal	100%	0%	100%	92%
Dry	100%	100%	100%	100%
Critical	0%	67%	0%	67%

**TF-1273**

San Joaquin Valley Index	No Carryover WQ	With Carryover WQ	No Carryover RF	With Carryover RF
Wet	100%	90%	100%	90%
Above Normal	100%	86%	100%	86%
Below Normal	100%	92%	100%	92%
Dry	100%	100%	100%	100%
Critical	100%	67%	100%	67%

**FG-800**

San Joaquin Valley Index	No Carryover WQ	With Carryover WQ	No Carryover RF	With Carryover RF
Wet	100%	90%	100%	90%
Above Normal	100%	86%	100%	0%
Below Normal	100%	92%	100%	92%
Dry	100%	100%	100%	100%
Critical	0%	67%	0%	67%