UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF RECLAMATION

MEMORANDUM TO CHIEF DESIGNING ENGINEER

SUBJECT: DIGEST OF TESTS OF STONE, PERCOLATION AND WATER

TABLE - MADDEN DAM

HYDRAULIC LABORATORY REPORT NO. .3

by

E. W. LANE

Under direction of

TECHNICAL MEMORANDUM NO. 125

Denver, Colorado

February 20, 1930

(PRICE \$0.25)

Denver, Colorado, February 20, 1930

Memorandum to the Chief Designing Engineer (E. W. Lane, Research Engineer)

Subject: Digest of Tests of Stone, Percolation, and Water Table.

Digest of Chemical Tests of Stone

| | Average Strata B | Average Strata |
|---|---------------------|-------------------|
| Phosphorus Pentozide P205 | 0.18 | 0.20 |
| Sulphur Trioxide SO3 | 0.6 | 0.2 |
| Total Alkalies Na ₂ O | 3.2 | 2.2 |
| Ignition Loss | 18.4 | 26.8 |
| Magnesia MgO | 3.1 | 3.0 |
| Calcium Oxide CaO | 16.3 | 26.4 |
| Alumna Al ₂ 0 ₃ | 16.0 | 11.9 |
| Total Iron Fe ₂ 0 ₃ | 5.8 | 3.4 |
| Silica SiO ₂ | 35.6 | 27.1 |
| Carbon Dioxide CO2 | 9.2 | 21.7 |

Digest of Physical Tests of Stone

| | Average Stratum B | Average Stratum C |
|--|-------------------------------|-------------------------------|
| Density, artificially dried, sp. gr. Lbs. per cu. ft. | 1.75 | 1.93 120 |
| Density, artificially saturated, sp. gr. Lbs. per cu. ft. | 2.049 127 | 2.206 137 |
| Apparent specific gravity | 1.72 | 1.92 |
| Specific gravity (as of cement) | 2.57 | 2.66 |
| Water absorbed, % by weight " " volume | 16.9 27.3 | 13.4 25.3 |
| Voids, % | 31.3 | 26.6 |
| Hardness (abrasive) | 3.8 | 2.4 |
| Linear dimension charge Perpendicular to bedding Original cond. to saturation, % """" dry, " Saturated to dry, " | +0.0023 -0.0589 -0.0612 | +0.0024 -0.0782 -0.0798 |
| Parallel to bedding direction A Original cond. to saturation, % " " dry, " Saturated to dry, " | +0.0008 -0.0352 -0.0360 | +0.0063 -0.0480 -0.0544 |
| Parallel to bedding direction B Original cond. to saturation, % " " dry, " Saturated to dry, " | +0.0039 -0.0394 -0.0433 | +0.0028 -0.0623 -0.0596 |
| Number of soaking and drying cycles producing disintegration | 10 | 15 |
| Number of cycles of boiling and drying producing disintegration | c- | 2 |

Digest of Compressive Tests on Stone of Foundation

| Six-Inch Cubes. | Normal to Bedding Plane. | | |
|---|--------------------------|---------------------------|------------------------------|
| | Average Strata B | | |
| Compressive strength on bed | | | |
| As received at laboratory | 1573 | 986 | |
| Artificially dried | 2675 | 2194 | |
| n saturated | 1367 | 897 | |
| After several drying and saturating cycles | 690 | (10) 325 (cycles) 310 | wet (4 cycles) (9 cycles) |
| Modulus of elasticity | | | |
| As received at laboratory | 628,000 | 522,000 | |
| Artificially dried | 567,000 | 420,000 | |
| " saturated | 462,000 | 320,000 | |
| Shearing across grain in condition received | 310 | | |
| Poisson's ratio | | | |
| As received at laboratory | 0.27 to | 1.06 0.34 | |
| Artificially dried | 0.25 to | 0.46 0.35 | |
| " saturated | 0.47 | 0.20 | to 0.35 |

A comparison was made of the compressive strength of drill cores from damsites No. 1 and No. 5. The results of these tests are shown graphically on Figure 1 attached hereto and summarized in the following table:

Comparison of Core Compressive Tests at Damsite No. 1 and No. 5.

| | : | | | | : Dam | site | :Av. | of old | l core | s:Av. of n | ew core | s: Av. of | all o | cores |
|-------------------------------|---------|--------|--------|-------|-------|-------|--------|---|---------------------------------------|------------|------------------------------------|-----------|---------|-------|
| Location | : Da | insite | No. | 1 | : N | 0. 5 | :Dam- | : Dam- | No. 1 | :Dam-:Dam | -: No. 1 | :Dam-:D | am-: No | 0. 1 |
| | : | | | | : | | :site | :site: | ex- | :site:sit | e:ex- | :site:s | ite:ex | c- |
| | | | | | : | | :No.1 | No. 5 | ceeds | :No.1:No. | 5:ceeds | :No.1:N | 0.5:ce | eds |
| | | | | | 0 | | : | | | : : | | : : | | 0. 5 |
| Holes | :L-1 : | L-2: | L-5: | L-6 | :L-3 | : L-4 | :L-1&: | THE RESERVE AND ADDRESS OF THE PARTY NAMED IN | THE RESERVE AND ADDRESS OF THE PARTY. | :L-58:L-4 | THE RESERVE OF THE PERSON NAMED IN | : L-1,: I | | |
| | : : | : | : | | | | :L-3 : | | | :L-6 : | : | :L-2,:L | -4: | |
| | : : | : | : | | | : | : | | | : : | | :1-5&: | : | |
| | : : | : | : | | | | 9 | | | : : | : | :L-6: | : | |
| | : : | : | : | | | | 6 1 | : | | : : | | : : | | |
| No. of tests | : 25: | 23: | 23: | 26: | 26 | 22 | | : | | : : | : | : : | 9 8 | |
| | : : | . : | | : | | | : | : | | : : | : | : : | | |
| Age when tested, days | : 216: | 257: | 29: | 26: | 241: | 31: | : 236: | 241: | | : 27: 3: | 1: | : 132: | 136: | |
| | : : | : | : | : | : | | : | . 1 | | : : | : | : : | : | |
| Max. compr. lbs./sq.in. | :1550: | 1775: | 2332: | 2620: | 1710: | 1933: | 1663: | 1710: | -3% | :2476:193 | 3: 28% | :2069:1 | 821: | 14% |
| | : : | : | : | : | : | | : | : | | : : . | 1 | : : | : | |
| Min. compr. lbs./sq.in. | : 607: | 602: | 1166: | 1292: | 150: | 799: | 604: | 150: | 300% | :1229: 79 | 7: 54% | : 917: 1 | 474: | 94% |
| | : : | : | : | : | | : | : | : | | : : | : | : : | | |
| Av. top 5, compr. lbs./sq.ir | 1:1101: | 870: | 2150: | 2226: | 567: | 1301: | 985: | 567: | 74% | :2188:1303 | : 68% | :1587: 9 | 934: ' | 70% |
| | : : | : | : | : | : | : | - | : | | : : | : | : : | : | |
| Av.top 10, compr. lbs./sq.in. | : 940: | 916: | 1803: | 1900: | 612: | 1352: | 928: | 612: | 51% | :1851:1352 | 2: 37% | :1339: 9 | 982: | 36% |
| | : : | : | : | : | : | : | : | 1 | | : : | : | : : | : | |
| Av. of all compr.lbs./sq.in. | :1029: | 997: | 1649:1 | 1737: | 772: | 1341: | 1013: | 772: | 32% | :1693:1343 | : 26% | :1353:10 |)56: | 28% |
| | : : | : | : | | : | : | : | : | | : : | * | : : | : | |

Applying this formula, assuming the ratio of peak to 24-hour flow at 1.53, as determined above, gives the following as the probability of floods at Alhajuela:

| | <u>Time</u> | Maximum Discharge to be Expected. Momentary | of Flood c.f.s. 24-hour |
|---------------------|-------------------------------|--|--|
| 5 10 25 50 | years years years years years | 41,300 94,200 117,000 147,200 170,000 192,800 | 27,000 61,600 76,500 96,200 111,100 126,000 |
| 400 | years | 240,000 | 156,000 |

The one and five-year floods of this table seem too high, but the 50 and 100-year frequencies are not unreasonable.

A study of the records of the 48 years beginning 1879 indicates alternate periods of high and low floods, beginning with 12 years of high floods, then 15 years of low floods, followed by 5 years of high, then 12 years of low and ending with 4 years (or more) of high floods.

From Memo. No. 3. Retention Volume Necessary. The purposes of the Madden Dam (Alhajuela project in order of importance are:

- (a) Increased water storage for dry season lockages, and incidental power production at Gatun, if practicable.
- (b) Flood control to obviate the necessity of excessive use of Gatun spillway to regulate the height of Gatun Lake.
- (c) Power production at Alhajuela.
- (d) Prevention of excessive currents in the canal channel at Gamboa. (This is of minor importance.)

Digest of Compressive Tests on Drill Cores from Foundation

A comparison of the strengths of Strata B and Strata C give the following results:

Average strength in lbs. per sq. in.

| | Strata B | Strata C |
|---------------------------------------|----------|----------|
| Compression as received | 1669 | 1528 |
| Artificially saturated | 1598 | 1427 |
| Oven-dried 110-120° C. | 2780 | 2462 |
| After 4 cycles dry to wet, tested wet | 319 | 901 |

Another test of the compressive strength of core samples from Strata B and C, 18 samples from each strata, from holes L-4 to L-9 inclusive gave the following results:

Compressive strength in lbs. per sq. in.

| | Strata B | Strata C |
|------------------------|----------|----------|
| As received | 1669 | 1528 |
| Artificially saturated | 1598 | 1427 |
| Oven-dried | 2780 | 2880 |

Summary of Percolation Tests

Cores from Madden Damsite

| Mark | | of water passed in | : of flow : with | :Av. increase in :solids content :of water parts : per million | |
|----------|---------|--------------------|------------------|--|-------------|
| T 1 D | : | : | : | 1 | 1 |
| L-4-B | | | : 0 | den minimum man | 2 martiners |
| -4-C | 1 | : 4 c. c. | : 0 | : 1283 | : 913 |
| -5-B | : +59.3 | : 0 | : 0 | 1 | 1 |
| -5-C | : -34.1 | : 65 | :Decrease | : 354 | : 173 |
| -6-B | : +712 | : 0 | : 0 | - | - |
| -6-C | : -24.1 | : 1 | : 0 | - | 1 |
| -7-B | : +43.1 | : 0 | : 0 | - | 1 |
| -7-C | : +13.6 | : 58 | :Decrease | : 1501 | : 1098 |
| -8-B | : +52.2 | : 1 | : 0 | : | 1 |
| -8-C · · | : +18.3 | : 19 | : 0 | 993 | 718 |
| | 1 | : | : | 9 | 1 |

Tests of Water Table

Records were kept of the elevation of the ground water in drill holes, in order to determine the position of the water table.

The results of the test are shown on Figure 2 attached hereto.

Weight of Concrete

Tests on the weight of concrete showed weights varying from 154 to 144.5 lbs. per cu. ft., generally close to 150 lbs. per cu. ft., with an average of 150.7 lbs. per cu. ft.