

HYD

HYDRAULICS BRANCH OFFICIAL FILE COPY

-3

18:

称: 奉

林 章

* *

彩 泽

* *

漆

*

4

*

*

-

救

4

**

HYD 16

*

埠

*

*

*

4

4

* *

*

*

*

* *

*

*

2

16

2

÷

10

李 蒋

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF RECLAMATION

MEMORANDUM TO CHIEF DESIGNING ENGINEER

HYDRAULIC MODEL STUDIES FOR THE DESIGN OF THE MARSHALL FORD DAM

Denver, **Colorado** February 1, 1937

HYB 16

1:5

HYD 16

BUREAU OF RECLAM

HYD- 16

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF RECLAMATION Debver, Colorado

February 1, 1937.

MEMORANDUM TO ASSISTANT CHIEF DESIGNING ENGINEER (J. E. Wernock and J. W. Ball)

Subject: Hydraulic model studies for the design of the Marshall Ford Dam.

1. <u>Introduction.</u> When a project involves the construction of two separate structures, as in the case of the initial and ultimate development of the Marshall Ford Dam, many features of the first structure must be designed for the more severe conditions encountered in the second. Two such features on the Marshall Ford Dam, outstanding from the hydraulic standpoint, are the training walls and the stilling pool. It was mainly for the purpose of determining the best design of these two features that a sectional model of the ultimate development was constructed at the Fort Collins laboratory.

The first plans of the ultimate development provided a 730-foot (gross length) uncontrolled overfall spillway; a siphon spillway, consisting of 28 individual siphons; and a set of 24 sluice conduits, for handling floods. These three methods of flood regulation combined in one structure made the stilling pool problem complicated and except for the siphons, pointed to the construction of a model which would include as much of the prototype as possible. The less-them-atmospheric pressure, present in siphos action, made a larger model more desirable so a sectional model on a scale ratio of 1:40.8 was built, figure 1. It included four siphons, four sluices, 105 feet of prototype crest and required a flow about equal to the maximum ospacity of the laboratory pump.

2. The Model.- A metal lined tank 11 feet long, 2 feet 6-7/8 inches wide and 8 feet deep was connected by a flange to one of the 24-inch conduits of the laboratory supply system. The upstream face of the model dam was installed at one end of the tank. The model under-structure was a framework of welded angle iron surmounted by 16-gage galvanized iron bests shaped nearly to the crest outline. A covering of 20-gage sheet metal geve the final shape of the model dam. An apron of sheet iron was festened to the floor and coldered to the model understructure. The flume, which contained the send bed and apron, extended 105 feet beyond the end of the apron. Glass panels were installed along one side to aid in visual studies as well as to facilitate photographing the stilling pool in action. The moden tellwater regulator, which was a gate hinged at the bottom, extended the full width of the flume. Regulation was obtained by a windlass and retchet mounted across the top of the flume. The metal siphons were attached to the model face by flenges. The parabolic curved sluice conduits were shaped from commercial brass tubing, the inside diameter (22 inches) determined the model scale ratio. The tubes were soldered at the downstream end and were held in place by flanges at the upper end. Each tube was provided with a bell-shaped entrence, figure 2.

TEST ON PRELIMINARY DESIGN STILLING POOL

3. <u>Initial Tests</u>.- Preliminary observations on the model with the original design of apron shown on figure 2, consisting mainly of visual tests, were made during the second week of December 1936. Very rough flow, ^Vattributed to the siphon jets, resulted. However, the siphons were eliminated from the design before organized testing of the model began, so test 1, and all subsequent tests were conducted accordingly.

The creat and sluices were calibrated individually and collectively to ascertain the prototype quantity represented on the model. Coefficient and discharge curves were prepared from these calibration data, figures 3 and 4. A study of these curves shows a reduced discharge through the sluices with flows over the creat. This reduction was attributed to the back pressures exerted on the exits of the sluice conduits by the spillway jet. Three possible operating conditions were studied; the sluices discharging alone, the sluices and creat discharging together and the creat discharging alone.

4. <u>Sluiges Discharging Alone.</u> Very satisfactory conditions provailed in the pool, with normal tailwater, when various quantities were passed through the sluices only, plate 1. The remote possibility of always operating all sluices at the same time with a low reservoir elevation led to further tests, in which an attempt was made to determine a satisfactory procedure for setting the aluiceways in operation when the reservoir surface was near the creat elevation. Sluice 1, nearest the powerhouse, was operated with a minimum tailwater to simulate conditions when opened with no flow in the river below the dam. At 5,000 second-feet the jet swept down the apron over the sill and excessively scoured the river_bed immediately downstream from the sill, plate 2. A dentated

sill was placed on the apron. Slight improvement was noted and a complete set of tests with various discharges and normal tailwater were made. A discharge of 2,000 second-feet gave conditions which, although not serious were not altogether desirable. The return flow on the apron. from the right crowded the jet against the wall of the model where rough conditions. with considerable splash resulted. Although the jet continued downstream over the sill, very little erosion was noted in the stream bed. plate 3. Sand was deposited on the apron to the right of this sluice. Discharges of 3,000 and 4,000 second-feet gave considerably worse conditions with excessive erosion immediately below the sill and more sand deposited on the apron, plate 4. Conditions were practically the same for sluices 1 and 2 discharging. plate 5. Three sluices operating improved conditions. However. the improvement may not be representative because of the narrowness of the model; also, some of the change was probably due to the deeper tailwater. A visual test with the two center sluices on the model operating gave fairly good results and it was believed that a systematic operation of the sluices, starting at the center of the spillway, might eliminate any danger to the toe of the apron. It was also believed, that much better conditions would result with the apron depressed in the region immediately below the 4:1 slope in the section containing sluices 5 and 6. The short sectional model prevented a satisfactory investigation either of the sluice operating program, or of the depressed section, and it was decided to build a model representing at least half of the spillway. Commercial size brass tubing and the laboratory pump capacity made a 1:68 scale the most desirable. The designs are practically completed and the model will be constructed immediately.

5. Crest and Sluiges Operating Together. - The second possible operating condition, crest and sluices operating simultaneously, was studied. Although the jump did not sweep off the apron at the higher discharges, the conditions in the pool were very rough, plate 6. The tailwater das despened until a very good jump formed. This procedure was followed in order to determine approximately the amount the apron should be lovered to obtain good conditions. The original 72-foot trapesoidal sill with a 2:1 sloping upstream face indicated that the apron should be lowered about 32 feet. figure 5. Then the same procedure was followed, with a 72-foot 1:1 sloping trapezoidal sill installed at the end of the apron, the pool became rougher and slightly additional depth was necessary to produce a satisfactory jump in the pool. A dentated sill installed on the apron considerably improved conditions with a satisfactory jump forming on the apron at normal tailwater, plate 7.

2

Comparative water surface profiles and erosion profiles along the center-line of the model flume were taken, figure 6. The dentated sill proved to be better than either the 2:1 or the 1:1 trapezoidal sill. More water was held on the apron and less erosion occurred downstream.

6. Discherges over Great Only .- The third possible operating condition, discharge over the crest only, was investigated. The sluices were closed and discharges from 40,000 to 360.000 second-feet, the latter about maximum reservoir elevation, were allowed to pass over the crest. The pool action (with 2:1 trapezoidal sill) was very desirable for flows up to and including 80,000 second feet, plates 8 and 9. For higher discharges the roughness of the pool increased and the jump formed downstress over the sill. The sheet of water entering the pool swept along the bottom and turned upward at the sill. Two rollers were formed, one back on the apron, and enother in the stream immediately below the sill. The 1:1 sloping trepesoidal sill gave practically the same results while the dentated sill showed considerable improvement. Because the crest is never likely to operate without the sluices and since the jump does not sweep entirely off the apron. the conditions encountered in these studies are not considered oritical. The pressure distribution on the crest was obtained, figure 7. All discharges below 360,000 second-feet produced positive or zero pressures. Slight negative pressure was noted at the downstream end of the parabolic curve for Xthis discharge. Because of the remote possibility of the occurrence of a flood of this magnitude and because of the pressures for the other flows, this condition is not considered critical.

7. <u>Training wall Tests.</u> The maximum water surface along the wall and the pressures in the pool (on both sides of the wall) will be obtained on the 1:65 model which is now under construction. Practically the same time will be required to construct this model as to alter the 1:40.8 model for obtaining the same data.

8. Conclusions .-

Sills. The 72-foot dentated sill was superior to the trapszoidal sills.

<u>Sluices only Operating.</u> Very good conditions will result when all sluices are opened under a low head and the reservoir and tailwater elevations increase simultaneously.

Opening sluise 1 or sluices 1 and 2, under high head, will give undesirable action in the stilling pool and cause excessive scour at the end of the apron and training well. Also, the opening of two adjacent sluices near the center of the spillway (under high head) would be undesirable because of the fin that forms between them when they spread on the apron. The fin shoots over the sill and might cause erosion of the stream bed. The operation of alternate or every third sluice might improve conditions. However, it is felt that a satisfactory solution of the sluice problem can only be obtained by studies on a model with more flexibility than the narrow one used for the tests discussed in this memorandum. The 1:68 model previously mentioned will serve to solve this problem satisfactorily.

Since and Great Operating Simultaneously.- Floods up to 500,000 second-feet can be efficiently handled when the sluices and creat operate together. The conditions in the stilling pool will be rough but the jump will always form on the apron.

<u>Creat Discharging Alone.</u> A very effective hydraulic jump will form on the aprox for all discharges up to approximately 100,000 second-feet. The pool will be rough for higher flows with the jump forming well out on the end of the apron and over the sill. Improvement will result if the sluices are set in operation before the discharge over the creat reaches 100,000 secondfeet.

Very <u>slight</u> negative pressures will occur on the creat for 360,000 second-feet. Practically zero pressures will exist for smaller discharges and the condition is not considered serious.

5

J. E. Wernock

J. W. Ball

List of Figures

Figure No.	Title	_No.	2
1	General Hodel Layout 2	49-2-13	-JWB-1
2	Details of Crest - Sluices, Aprons and Sills Tested.	8	* -2
3	Discharge Coefficient - Crest and Sluice	9 ¹¹	⁸ -10
4	Discharge Curves - Original Apron	99	* -11
5	Jump Height Curves	n	r -12
6	Scour and Nator Surface Profiles	*	[#] -14
7	Pressures on Crest	ħ	* -13

List of Plates

Figure	Title				
1	All Sluices Discharging - Normal Tailwater				
2	Sluice No. 1 only Discharging - Minimum Tailwater				
3	Sluice No. 1 only Discharging - Normal Tailwate r				
4	Sluice No. 1 only Discharging - Normal Tailwater				
5	Sluices 1 and 2 Discharging - Normal Tailwater				
6	Stilling pool action with 2:1 Trepszoidal Sill Crest and Sluices Discharging.				
7	Stilling Pool Action with Dentated Sill, Grest and Sluices Discharging.				

3

8 Stilling Pool Action with 2:1 Trapezoidal Sill Crest only Discharging.

9 Stilling pool action with 2:1 Trapszoidal Sill Crest only Discharging.

6





FIGURE 2 Ana. m SIG PLAN OF DENTATED SILL 1-3% -181-E1. 487.0 JE1. 480.0 1 EI. 479.75 DENTATED SILL ~ TEST 7; TESTS 9 INCLUSIVE TO 11 INCLUSIVE & TESTS 14 TO_ -2%-1% - E1.487.0 El. 480.0 EI 979.75 2'-7-2 1 TO1 TRAPEZOIDAL SILL - TEST 12 - 4 /A - 1/B E1 48 2-2 JE1 980 El. 479.7 DEPARTMENT OF THE INTERIOR BUREAU OF RECLAMATION COLORADO RIVER PROJECT - TEXAS 2 TO1 TRAPEZOIDAL SILL MARSHALL FORD DAM HYDRAULIC MODEL STUDIES ULTIMATE DEVELOPMENT ~ MODEL SCALE 1 TO 423, DETAILS OF CREST, SLUICES, APRONS & SILLS TESTED TESTS 1TO 5 INCLUSIVE TESTS 8 & 13 DRAWN R.A.G. SUBMITTED RECOMMENDED TRACED CHECKED APPROVED 49-2-12-JWB-2FT COLLINS, COLO. JON 18







FIGURE 5 AFF DISC 8 NOR MAL TAIL WATER CUR LFGEND 1E57 5-OWET TAHING GIVING -0 0 SATISFAT DAY JUM SATISTATTO GIVIALS MA TEST 8 --AiA TAIT TAN TAN GANAN TFST 12 -Y Aris SAFISFACTURE JUNE Test 5 e a 21 15ill on ariginal Abrow NOTE Tast 10 with Dentoted Sill on Original Apron 440 480 520 MARSHALL PORD DAM FINAL DEVELOPATENT - MODEL SCAL JUMP HENGHT CURVES DRAWN RASS D.ML SUSATTED 360 400 E 1:400 20 7RACED RESCONTER CHIEFED APPROVED 2407-2472 FT. COLLINS, COLO. 1/4,37 HECOMMENCE. APPROVER



	_		-		
112211	11-111			1-1-11	Flandt 6
-	HART				
-					
			1112111-0		
- 8			Frank P		
		.0			
				111	
	-		-		a man 110
				4445	
					1307392072 [/]
	-a				FACE Q1/25,000 CAS
					HATZA ILANDER BANAZON FAT
		I. I		·****	
• 	-	11212111			SCOUR AFTER OUSDODDEFS
		-			
			1111		
-			THE PLAT		
		11.2.1.1.1.1.1			
				4777	
-					
-0+		6	70	7	7/0
	± :-				
1000		121-121			0
			D		
Ball	11			11121111	
1	111-11-1		1.1.1		TABULATON DE
	-		14		S CTEASE FLORE LONGINGE
				-	SEC. F.F. OF FLOW TIME
			11 1 1 1 2		
111		11000111	14	11111111	300,000 -35 1200 000 1000 10
					STRUCTURE THE PART AND ADDRESS TO THE STRUCTURE
	-	1	A Property lines		$\frac{1}{D_{1}} = \frac{1}{2} \left[\frac{1}{2$
	Inclini	12111111	1	-int	Transferrate the second
				-14-1-1	
-					
-				-D	
1				-	
				1111111111	
-0-		Pp+ r			בוויישר על החתומיו לכ הה יעול היידמאו
61	5	6	10	7	in These Tests.
					Scour no meastrais
					01 0.125050 G.F.S With 1
					dental od. SILL:
1					Normal Taitwater
-0	- 22-				used auring These resis
		- mi-	17		
			-	-	
1					
		-Der antere			
			1.0	- 126	
	0	······································	() (O		
-				+	
					DEPLAZMENT OF THE ILL THE ST
		0	1000	0	COLORADI R' IN RADUTETA IL MIS
	100	1 0			NAESIN' FORD DAM
				-	ANDRA LLIS MODEL STOLLET
				11	true DEVELOXMANN - HATTLE STALL HAVE
			Ð	F	SCOULT S WATER TURITIES REPORT IS
	-		-	DR	RANK C. M. SUBMITTER
15			12.7	7.4	1555 BEC 22 PULL 252
				1 de	13 /2 J. 1. 1.
_	_				4 16 - 11 - 3.4 : 11 - 4.8 x







After Discharge of 120,000 Second-feet



Discharge 100,000 Second-feet

Before Test



Discharge 60,000 Second-feet









Discharge 80,000 Second-feet



1. 1. 1. 1.



















Discharge 5,000 Second-feet



Discharge 5,000 Second-feet



After Discharge of 5,000 Second-feet

ACTION OF SLUICE 1. DISCHARGING - MINIMUM TAIL.ATER 74-FOOT 2:1 TRAPEZOIDAL SILL



After Discharge 5,000 Second-feet

Discharge 5,000 Second-feet

1 4 1 1

SIJICE 1 ONLY OPER TING - NORMAL TAIL 1. TER - 74-FOOT DENTATED SILL

PLAPE 3.





Discharge 4,000 Second-feet



Discharge 3,000 Second-feet



After Discharge of 5,000 Jecond-feet



Discharge 5,000 Second-feet

ACTION JITH SLUICE NO.1 OPERATING - LOR. AL TAIL ATER

74-FOOT DENTATED SILL





Discharge 6,000 second-feet

ACTION OF SLUICES 1 AND 2 OPERATING - NORMAL TAIL AT R - 72-FOOT DEMTATED SILL



Tailwater 2.4 Feet above Normal



Tailwater 4.0 Feet above Normal

Normal Tailwater

Discharge 500,000 Second-feet

STILLING POOL ACTION - SLUICES AND CREST DISCHARGING - 74-FOOT 2:1 TRAPEZOIDAL SILL

FLATE 6.



n Constant (199

STILLING POOL ACTION - SLUICES AND CREST DISCHARGING - DENTATED SILL.

JLATE 7.









Discharge 120,000 Second-feet



Discharge 60,000 Jecond-feet



Discharge 120,000 Lecond-feet

STILLING POOL ACTION - CREST ONLY DISCHARGING - NORMAL TAIL ATER $7\frac{1}{4}$ -FOOT 2:1 TRAPEZOIDAL SILL,



FLITE 9.

Tailwater 7.4 Feet above Normal

Normal Tailwater Discharge 360,000 Second-feet

STILLING POOL ACTION - CREST ONLY DISCHARGING - 74-FOOT 2:1 TRAPEZOIDAL SILL



Crest and Sluices Discharging.

10

ACTION OF STILLING POOL - 200-FOOT RADIUS BUCKET - 4:1 SLOPING APRON - DENTATED SILL

-



Discharge 300,000 Second-feet

Discharge 240,000 Second-feet





Tailwater 0.9 Feet above Normal



11.120v

Normal Tailwater

INTIGA4







Normal Tailwater

Normal Tailwater



Tailwater 2.2 Feet above Normal

FLATE

E

Discharge 500,000 Second-feet

STILLING POOL ACTION CREST AND SLUICES DISCHARGING 200-FOOT RADIUS BUCKET - 4:1 SLOPING APRON - DENTATED SILL.