


# Project A: Streamflow, Water Quality, and Sediment Transport and Budgeting in the Colorado River Ecosystem

We collect, post, and analyze the following data at stations located through the Colorado River Ecosystem, including key tributaries...

- **Element 1: Stream gaging**
  - Stage
  - Discharge
- **Element 2: Water quality**
  - Water temperature
  - Salinity (specific conductance)
  - Turbidity
  - Dissolved Oxygen
- **Element 3: Sediment transport and budgeting**
  - Suspended- and bed-sediment data
  - Sediment loads (silt and clay loads and sand loads)
  - User-interactive sand budgets in 6 reaches from Lees Ferry to Lake Mead
- **All elements**
  - User-interactive duration-curve tool for any continuous parameter



Almost all other projects funded by the Glen Canyon Dam Adaptive Management Program (GCDAMP) use these data, and data from this project informs 10 LTEMP goals

Funding: GCDAMP provided \$1.15 million during FY 2022

# Evaluation of LTEMP sand management







David J. Topping, U.S. Geological Survey  
Paul E. Grams , U.S. Geological Survey  
Ronald E. Griffiths, U.S. Geological Survey  
Matt Kaplinski, U.S. Geological Survey  
Joel A. Unema, U.S. Geological Survey  
David J. Dean, U.S. Geological Survey  
Katie A. Chapman, Northern Arizona University  
Joseph E. Hazel, Jr.

The information in several of these slides is preliminary and is subject to revision. It is being provided to meet the need for timely best science. The information is provided on the condition that neither the U.S. Geological Survey nor the U.S. Government shall be held liable for any damages resulting from the authorized or unauthorized use of the information.

# Downward spiral has likely occurred in long-term sand mass balance... and reflected in the high-elevation volume of an unknown percentage of the sandbars

>28 million metric tons of sand eroded since 1963, mostly during 3–4 periods of sustained high dam releases (Topping and others, *JGR*, 2021)

~12 million metric tons eroded in late 1990s alone (6 from Marble and 6 from Grand)



# Some of the sand involved in sandbar deposition during HFEs is part of a “bank account” that cannot be replaced

- Although the Paria River is by far the dominant modern supplier of sand (Topping and others, *JGR*, 2021), a large percentage (~30–50%) of the sand stored in sandbars is relict “pre-dam” sand (Chapman and others, *GSA Bulletin*, 2020)
- Stratigraphic and ground-penetrating-radar data suggest strongly that pre-dam sand exists at depth in at least some sandbars (Barnhardt and others, *USGS-OFR*, 2001)








Figure modified from Hazel and others (USGS-PP, 2022)

67% of the long-term sandbar monitoring sites in Marble Canyon had less high-elevation sand in October 2022 than in June 1990,



whereas only 11% of the long-term sites in Grand Canyon had less high-elevation sand in October 2022 than in June 1990

# High-elevation sand at many of the long-term sandbar monitoring sites in Marble Canyon defines a downward spiral





Only repeated sand-enriched HFEs may reverse this trend,  
as during 2012–2014

Data from 37 surveys depicted; data from USGS (2023a)



Sustainable management of sand under the LTEMP sediment goal thus requires neutral to positive trends in both the sand mass balance (i.e., the bank account) and the high-elevation sandbar volume (i.e., your expenditures) over decades

Scenario 1





Not sustainable

Scenario 2



Not sustainable  
Bank account mined to  
deposit sandbars  
"Living on credit"


Scenario 3




Sustainable  
"Living  
within your  
means"



# Metrics Example: The Bank Account




**POSSIBLE SUCCESS!** Sustainable in Lower Marble Canyon if high-elevation sandbar volume is positive during this period.




**POSSIBLE FAILURE** Not sustainable in Eastern Grand Canyon regardless of whether high-elevation sandbar volume is positive during this period.

# Conducting sand-enriched HFEs at every opportunity is central to the LTEMP experimental design


...in future controlled floods, **more sand is required** to achieve increases in the total area and volume of eddy sandbars throughout all of Marble and Grand Canyons. Annual tributary inputs of sand much larger than one million metric tons occur but are relatively rare. Therefore, “more sand” could be achieved directly by **augmentation** from sand trapped in the reservoir impounded by Glen Canyon Dam or perhaps indirectly **by following each large tributary input of sand with short-duration controlled floods**. **Frequent short-duration controlled floods under sand-enriched conditions could result in the downstream propagation (into the downstream half of Marble Canyon and into Grand Canyon) of the gains in total eddy-sandbar area and volume observed in the upstream half of Marble Canyon during the 2004 controlled-flood experiment.**



# HFE-Protocol Period Upper Marble Canyon




POSITIVE




POSITIVE


Possibly sustainable



# HFE-Protocol Period Lower Marble Canyon




POSITIVE




POSITIVE


Possibly sustainable



# HFE-Protocol Period Eastern Grand Canyon




NEGATIVE




POSITIVE


NOT sustainable



# HFE-Protocol Period East-Central Grand Canyon




POSITIVE




POSITIVE

Possibly sustainable


Data from USGS (2023a, b)



# HFE-Protocol Period West-Central Grand Canyon



INDETERMINATE




POSITIVE


Possibly sustainable

# Unanticipated 4<sup>th</sup> scenario

## “Abandonment of the experimental design”




Sandbars erode to low levels perhaps difficult to recover from




Export rate increases as bed-sand fines






# LTEMP Period Upper Marble Canyon




POSITIVE




NEGATIVE

Failing to follow LTEMP experimental design; sandbar erosion


Data from USGS (2023a, b)



# LTEMP Period Lower Marble Canyon




POSITIVE




NEGATIVE

Failing to follow LTEMP experimental design; sandbar erosion


Data from USGS (2023a, b)



# LTEMP Period Eastern Grand Canyon




INDETERMINATE





NEGATIVE

Failing to follow LTEMP experimental design; sandbar erosion

Data from USGS (2023a, b)



# LTEMP Period East-Central Grand Canyon




BARELY INDETERMINATE



NEGATIVE

Failing to follow LTEMP experimental design; sandbar erosion

Data from USGS (2023a, b)



# LTEMP Period West-Central Grand Canyon



LIKELY POSITIVE

ZERO SLOPE

Sustainable ?

Sandbars starting to degrade

Data from USGS (2023a, b)

# Tributary sand inputs increase storage and EXPORT





Figure from Topping and others (JGR, 2021)


- July 1, 2020, to first Paria River flood in 2021
- First Paria flood in 2021 to first Paria flood in 2022
- After first Paria flood in 2022



Data from USGS (2023b)

Bed-sand fining offsets effect on sand transport of lower dam releases

Despite similar sand-supply magnitudes, sand retention decreased faster between 2021 and 2022 than did discharge



Data from USGS (2023b)

# Conclusions

- LTEMP sand management is failing because of the abandonment of the experimental design
- 6 years of LTEMP, 3 HFE triggers, only 1 HFE
- Dam maintenance schedule has also compromised LTEMP; last full-magnitude HFE was in 2012
- A substantial number of sandbars in Marble Canyon are at their lowest condition since monitoring began
- Although sandbar gains did occur during the HFE-Protocol period, it remains unclear if it is possible to rebuild sandbars to their early 1990s condition because of the large amount of sand eroded during the high flows of the late 1990s (1997 had the second longest period of sustained high discharge after 1984; Topping and others, *USGS-PP*, 2003)
- LTEMP may reach its conclusion and we may still not know if sustainable sand management is possible





Thank you

# References

- Barnhardt, W.A., Kayen, R., Rubin, D., and Minasian, D.L., 2001, The internal structure of sand bars on the Colorado River, Grand Canyon, as determined by ground-penetrating radar: *U.S. Geological Survey Open-File Report 2001-425*, 74 p. <https://doi.org/10.3133/ofr01425>
- Chapman, K.A., Best, R.J., Smith, M.E., Mueller, E.R., Grams, P.E., and Parnell, R.A., 2020, Estimating the contribution of tributary sand inputs to controlled flood deposits for sandbar restoration using elemental tracers, Colorado River, Grand Canyon National Park, Arizona: *Geological Society of America Bulletin*, v. 133, p. 1141–1156. <https://doi.org/10.1130/B35642.1>
- Hazel, J.E., Jr., Kaplinski, M.A., Hamill, D., Buscombe, D., Mueller, E.R., Ross, R.P., Kohl, K., and Grams, P.E., 2022, Multi-decadal sandbar response to flow management downstream from a large dam—The Glen Canyon Dam on the Colorado River in Marble and Grand Canyons, Arizona: *U.S. Geological Survey Professional Paper 1873*, 104 p., <https://doi.org/10.3133/pp1873>
- Topping, D.J., Rubin, D.M., Schmidt, J.C., Hazel, J.E., Jr., Melis, T.S., Wright, S.A., Kaplinski, M., Draut, A.E., and Breedlove, M.J., 2006, Comparison of sediment-transport and bar-response results from the 1996 and 2004 controlled-flood experiments on the Colorado River in Grand Canyon: *Proceedings of the 8th Federal Inter-Agency Sedimentation Conference*, Reno, Nevada, April 2-6, 2006, [http://acwi.gov/sos/pubs/8thFISC/Session 1B-3 Topping.pdf](http://acwi.gov/sos/pubs/8thFISC/Session%201B-3_Topping.pdf)
- Topping, D.J., Grams, P.E., Griffiths, R.E., Dean, D.J., Wright, S.A., and Unema, J.A., 2021, Self-limitation of sand storage in a bedrock-canyon river arising from the interaction of flow and grain size: *Journal of Geophysical Research: Earth Surface*, v. 126, e2020JF005565. <https://doi.org/10.1029/2020JF005565>
- U.S. Geological Survey, 2023a, Grand Canyon sandbar monitoring, Grand Canyon Monitoring and Research Center: accessed on January 13, 2023, at <http://www.usgs.gov/apps/sandbar/>
- U.S. Geological Survey, 2023b, Discharge, sediment, and water quality monitoring, Grand Canyon Monitoring and Research Center: accessed on January 13, 2023, at [http://www.gcmrc.gov/discharge\\_qw\\_sediment/](http://www.gcmrc.gov/discharge_qw_sediment/)

Project A work completed in FY 2022 addressed the following two hypotheses paraphrased from the Glen Canyon Dam Long-Term Experimental and Management Plan (LTEMP) Environmental Impact Statement (EIS) and earlier GCDAMP documents

- Glen Canyon Dam can be operated such that the sand resources in the Colorado River ecosystem (CRe) are sustainable.
- Glen Canyon Dam can be operated such that the other CRe resources affected by dam operations can be sustainably managed. In this usage, “dam operations” refers to the amount and quality of the water released from the dam, where “amount” refers to stage and streamflow, and “quality” refers to temperature, salinity, turbidity, and dissolved oxygen.

### FY 2022 products

- All required monitoring data collected but only **LARGELY** processed and posted to Project A’s website ([https://www.gcmrc.gov/discharge\\_qw\\_sediment/](https://www.gcmrc.gov/discharge_qw_sediment/)) and to NWIS
- 1 peer-reviewed journal article in the *Proceedings of the National Academy of Sciences NEXUS*, 1 peer-reviewed article in *Water Resources Research*, and 1 USGS OFR published; 1 USGS Professional Paper in press and 1 USGS OFR through review (see list in Annual Report)