

Glen Canyon Dam Adaptive Management Program Adaptive Management Work Group Meeting November 7, 2023

Paul Grams
U.S. Geological Survey
Southwest Biological Science Center
Grand Canyon Monitoring and Research Center

This information is preliminary and is subject to revision. It is being provided to meet the need for timely best science. The information is provided on the condition that neither the U.S. Geological Survey nor the U.S. Government shall be held liable for any damages resulting from the authorized or unauthorized use of the information.

# Acknowledgements

#### Website:

Bob Tusso

https://www.usgs.gov/apps/sandbar/

Or

www.gcmrc.gov/sandbar/

#### **Suspended Sediment:**

David Topping and Project A staff

#### **Remote Camera Downloads:**


Bob Tusso and Katie Chapman

#### **Columbine Reach Surveys:**

Paul Grams, Katie Chapman, Matt Kaplinski, Erica Byerley, Gerard Salter, Shannon Sartain, Karen Koestner, and Keith Kohl




### April 2023 HFE – Planned and observed discharge



https://www.usbr.gov/uc/progact/amp/ltemp.html


5,000 cfs of tributary inflows during HFE!



- $\sim$ 40,000 cfs at Lees Ferry, RM 30, and RM 61
- ~42,000 cfs at RM 87
- ~45,000 cfs at RM 165 and 225



#### April 2023 HFE – modeled vs. observed sediment balance




Model-predicted 1-year sediment budget (7/1/2022 to 7/1/2023)

Figure 3. Mass balance in Marble Canyon predicted by the Sand Routing Model (Wright et al. 2010) with a 1-year accounting window and a 72-hour HFE in April with a maximum magnitude of 39,500 cfs.

HFE for 72-hours at ~40,000 cfs was designed based on sand that
accumulated in Marble Canyon from July 1, 2022 through October 2022
and remained in Marble Canyon during the low winter 2022/2023 releases.




#### April 2023 HFE – modeled vs. observed sediment balance



Model-predicted 1-year sediment budget (7/1/2022 to 7/1/2023)

Figure 3. Mass balance in Marble Canyon predicted by the Sand Routing Model (Wright et al. 2010) with a 1-year accounting window and a 72-hour HFE in April with a maximum magnitude of 39,500 cfs.




Measured 1-year sediment budget (7/1/2022 to 7/1/2023)

Modeled and measured budgets agree within uncertainty



# Summer reservoir balancing releases exported more sand from Marble Canyon than April HFE




The sand exported by HFEs is the "cost" for accomplishing the goal of building sandbars at high-elevations

The sand exported during May-Aug releases includes erosion of some of the HFE deposits and some redeposition at lower elevations



# Reservoir equalization/balancing releases export 3 to 5 times more sand than average summer releases



May-Aug sand load in 2011 was ~2.3 million metric tons


May-Aug sand load in 2023 was ~1.5 million metric tons

Average May-Aug sand load for 2012-2022 was 428,000 metric tons



## Preliminary Remote Camera Results from April HFE


- At least some deposition at more than 85% of monitoring sites with remote cameras
- At some sites, deposition was offset by erosion
- Vegetation scour or burial at many sites
- Gullies eroded by monsoon storms filled
- Similar number of gainers compared to previous HFEs.
  - Different water levels make comparison with previous
     HFEs difficult





## Preliminary Remote Camera Results from April HFE

- At least some deposition at more than 85% of monitoring sites with remote cameras
- At some sites, deposition was offset by erosion
- Vegetation scour or burial at many sites
- Gullies eroded by monsoon storms filled
- Similar number of gainers compared to previous HFEs.
  - Different water levels make comparison with previous
     HFEs difficult



Number of sand "gainers" for each HFE








HFE resulted in highelevation deposition and filled gullies





High-elevation HFE deposits remain.

Mid-elevation HFE deposits eroded.







HFE resulted in highelevation deposition and scoured/buried vegetation










High-elevation HFE deposits eroded.

> Replaced by lowelevation deposit



### Pumpkin Springs Camp – River Mile 213, Left



#### Pumpkin Springs Camp – River Mile 213, Left



HFE resulted in highelevation deposition and scoured/buried vegetation

#### Pumpkin Springs Camp – River Mile 213, Left



High-elevation HFE deposits eroded.

#### Summary

- Substantial deposition at most sites from Upper Marble Canyon to Diamond Creek
- Magnitude of sandbar building was comparable to previous HFEs
- Reservoir balancing flows in May-August exported ~1.5 million tons (+/-20%) of sand past Diamond Creek, 3 times more than average for that period
- High dam releases caused substantial erosion, but HFE deposits do remain
- Low releases in September and October exposed low-elevation sand deposits
- We will report on results from October sandbar survey at Annual Reporting Meeting

#### Website:

https://www.usgs.gov/apps/sandbar/

