

RECLAMATION

Managing Water in the West

Grand Canyon Sediment Augmentation Study

Tim Randle, P.E.

**Manager, Sedimentation and River
Hydraulics Group, Denver, Colorado**



U.S. Department of the Interior
Bureau of Reclamation

Sediment Augmentation Objectives

- Seasonally increase turbidity to provide cover for native fish.
- Annually increase sand supply to build larger sandbars, in conjunction with beach-building flows.

RECLAMATION

Sediment Augmentation Plan

- Increase turbidity by continuously supplying silt- or clay-sized sediments from May through December to produce suspended sediment concentrations of 500 ppm (3 million tons per season).
- Annually supply 1 million tons of sand to Grand Canyon.

RECLAMATION

Study Team

- Reclamation Engineers
 - Tim Randle (overall guidance)
 - Joe Lyons (team leader)
 - Ron Ferrari (Lake Powell survey)
 - Jim Yahnke (water quality)
 - Fred Tan (pipeline design)
 - Rick Christensen (sediment dredging)
 - Richard Fehr (pumping plant design)
 - Lisa Gamuciello (electrical power)
 - Larry Rossi (electrical controls)
 - Jerry Zander (cost estimation)

Study Team (continued)

- National Park Service
 - Norm Henderson (plan formulation)

Types of Sediment Augmentation Alternatives

- Alternative sediment sources
- Alternative points of delivery
- Alternative delivery methods




RECLAMATION

Alternative Sediment Sources

- Lake Powell Deltas
- Lake Mead Delta
- Other Terrestrial Site

RECLAMATION


Lake Powell Deltas



Dirty Devil River



Colorado River



Escalante River



San Juan River



Navajo Canyon



Glen Canyon Dam



3 9:51 AM

RECLAMATION

Sediment Source near Glen Canyon




RECLAMATION

Navajo Canyon Delta



RECLAMATION


Navajo Canyon Survey



December 2004

RECLAMATION

Navajo Canyon Profile




Navajo Canyon Sedimentation

- Maximum sedimentation volume of 40 million m³ (30,000 acre-feet) since 1963
- Maximum sediment mass of 40 million tons
- Average annual sedimentation rate of 1 million tons per year

RECLAMATION

Navajo Canyon Sediment Sustainability




Sediment Size and Quality of One Delta Sample

- 57 % silt and clay
- 43 % sand
 - 30 % very fine sand
 - 13 % medium sand
- Angular quartz particles have high potential for abrasion of pipes, valves, and pumps
- Sample was analyzed for 39 elements
 - no contaminants were found



Alternative Points of Delivery



RECLAMATION

Sediment Discharge Locations

- Below Glen Canyon Dam
 - Sand: continuous year-round discharge
 - Silt and clay: continuous, seasonal discharge
- Lees Ferry
 - Sand: stock pile and discharge before beach-building flow
 - Silt and clay: continuous, seasonal discharge

RECLAMATION

Alternative Delivery Methods

- Barge and truck
- Sediment slurry pipeline

RECLAMATION

Barge and Truck Alternative Eliminated

- Excessive barge traffic on Lake Powell
 - Barge size: 30 m x 10 m (100 ft x 30 ft)
 - 37 barge trips per day for sand
 - 135 barge trips per day for silt and clay
- Excessive truck traffic on highway between Page and Lees Ferry
 - 130 truck trips per day for sand
 - 500 truck trips per day for silt and clay

RECLAMATION

Sediment Slurry Pipeline Alignments

- Overland from Navajo Canyon
- Submerged in Lake Powell



RECLAMATION

Overland Pipeline Alignment Eliminated

- Steep bedrock topography of Navajo Canyon has more than 300 m (1,000 ft) of vertical rise
- No roads cross this pristine area
- A floating pipeline would still be required to deliver sediment from the dredging operation to the overland pipeline


Lake Powell Slurry Pipeline Alignment




RECLAMATION

Sediment Slurry Pipeline Alignment

TOPOI map printed on 01/04/06 from "GCSedimentAugmentationDSDam.tpo"



Sediment Slurry Pipeline: Navajo Canyon to Lees Ferry




Sediment Slurry Pipeline Lengths

- Navajo Canyon to Glen Canyon Dam
 - 28.2 km (17.5 miles) of submerged pipeline
 - 13.8 km (8.6 miles) of buried pipeline
- Navajo Canyon to Lees Ferry
 - 28.2 km (17.5 miles) of submerged pipeline
 - 79.3 km (49.3 miles) of buried pipeline

Submerged Pipelines



Buoy



Sand Slurry Pipeline Dimensions

- Three, 12-inch (0.30 m), pipes
 - HDPE (High Density Polyethylene)
- Total flow rate of 4.4 ft³/s (0.12 m³/s)
- 15 % sand concentration
- Annual water volume of 3,000 acre-feet per year (4 million m³/yr)

Silt/clay Slurry Pipeline Dimensions


- Three, 24-inch (0.61 m), pipes
 - HDPE (High Density Polyethylene)
- Total flow rate of 27 ft³/s (0.76 m³/s)
- 20 % silt/clay concentration
- Annual water volume of 13,000 acre-feet per year (16 million m³/yr)

Land-based Pumping Plants



Building size:

- 9 m (30 ft) wide
- 18 m (60 ft) long
- 3 m (10 ft) high



RECLAMATION

Floating Pumping Plants

Modular barge size:

- 3 m (10 ft) wide
- 12 m (40 ft) long
- 2 m (7 ft) deep



RECLAMATION

Sediment Slurry Pumping Plants

- Navajo Canyon to Glen Canyon Dam
 - 3 floating pumping plants
 - 4 land-based pumping plants
- Navajo Canyon to Lees Ferry
 - 3 floating pumping plants
 - 17 land-based pumping plants

Navajo Canyon Dredging Operation


Near continuous operation
of clamshell dredge



RECLAMATION

3:1:24 PM

Sediment Slurry Pipeline Navajo Canyon to Lees Ferry



Sand Storage near Lees Ferry

- Two basins would alternatively be used to settle the sand from the slurry pipeline.
- Each basin would be 275 m by 75 m (900 feet by 250 feet) and would fill in about one month.

Sand Storage near Lees Ferry

- Bulldozers, loaders, and trucks would remove the sand from each basin.
- 1 million tons of sand would be stored near the Colorado River.
- Sand storage volume
 - 190 m by 190 m (630 ft by 630 ft)
 - 15 m (50 ft) high
- Pushed into river by bulldozers (D-10)

RECLAMATION

Costs

- Appraisal-level cost estimates are in progress?

RECLAMATION

Conclusions

- A sediment slurry pipeline is technically feasible.
- No environmental problems have been identified at this time.
- Attempts have been made to avoid cultural resources impacts.
- Augmentation of fine sediment should be considered with selective withdrawal.

RECLAMATION

Next Steps

- Cost estimates are in progress
- Finalize the report
- If there is stakeholder interest:
 - More sampling and testing of sediments
 - Feasibility design to Congress
 - Congressional authorization
 - Final design
 - Construction bids

RECLAMATION